

**RELIABILITY TEST PROCEDURES FOR ECS-320-CDX-2374**



| <u>NO.</u> | <u>TEST NAME</u>   | <u>TEST PROCEDURES</u>   | <u>REQUIREMENTS</u>                                       |
|------------|--|--|---|
| 1          | <b>SHOCK</b>   | Drop 3 times from the height of 100cm onto hard wooden board.  | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 2          | <b>VIBRATION</b>   | Vibration Frequency: 10 to 55Hz, 1.5mm, full wave<br>Cycle: 2 min.<br>Direction: X.Y.Z.<br>Time: 2 hours in each direction   | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 3          | <b>STORAGE IN HIGH TEMPERATURE</b>                             | +85 ±2°C for 500 hours.  | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 4          | <b>STORAGE IN LOW TEMPERATURE</b>                              | -40 ±2°C for 500 hours.  | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 5          | <b>RESISTANCE TO SOLDERING HEAT</b>                            | Pass through reflow for 10s (Max.) which is pre-heated at a temperature of 160°C ± 10°C and 240°C ± 5°C  | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 6          | <b>HUMIDITY</b>  | + 60 ± 2°C in humidity<br>95% for 500 hours.   | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 7          | <b>THERMAL SHOCK</b>   | Supply 500 cycles as follows:<br>Temperature shift shall be done within 30 sec.<br>-55 ±2°C    +125 ±2°C<br>(30 min) <-----> (30 min)  | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 8          | <b>TEMPERATURE CYCLE</b>                                       | <p>Supply 100 cycles as follows:</p> <p>The diagram shows a temperature profile for one cycle. It starts at +25 ±5°C for 10 minutes, then drops to -55 ±3.5°C for 30 minutes, then rises back to +25 ±5°C for 10 minutes, and finally rises to +125 ±5 -2°C for 30 minutes before returning to the start. The entire sequence is labeled as '1 Cycle'.</p> | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 9          | <b>SEALING TIGHTNESS MIL-STD 202F METHOD 112D TEST C AND D</b> | 1) Dipping in Florinert at:<br>+125 ±5°C for 5 min.<br>(Gross Leak)  | There are no visual abnormalities.                        |
|            |  | 2) Leak rate shall be measured by using:<br><br>Helium leak Detector<br>(Fine Leak)  | There are no visual abnormalities.                        |
| 10         | <b>Mean Time Between Failures (MTBF)</b>                       | $MTBF (25°C) = \frac{E_a \times (1/T_1 - 1/T_2) / K}{\pi}$   | 16396600 Hours  |